PEX Insert Connecters for 1-¼" Stainless Steel Manifolds

Job or Customer :	
Location :	
Engineer :	
☐ Complies with Spec ☐ Alternate	Notes :
Contractor :	
HeatLink Rep :	
Submitted By :	Date :
Approved By :	Date :
P.O. Number :	Date :

Description

Solid brass fitting is installed into the bottom of the manifold and is held in place by the nut. The tubing is then pressed on to this fitting. Comes with o-ring. SS press sleeves sold separately. *Not for potable water use.*

Pair Qty	Stk. #	PEX Size	A in (mm)	B in (mm)	Weight lb (kg)
	77305	½"	1.30 (33)	0.79 (20)	0.47 (0.213)



Technical Data

	Specifications
Operating temperature	160°F (70°C)
Minimum temperature	32°F (0°C)
Maximum temperature	230°F (110°C)
Max working pressure	100 psi (6.9 bar)

Standards

ASTM F1807



Installation

Installation must follow all of HeatLink's instructions and guidelines.

Maintenance

Maintenance must follow all of HeatLink's instructions and guidelines.

Related Documents

- 1-¼" Stainless Steel Manifold Assembly Instructions (L676100)
- HeatLink Limited Heating Warranty

All information is subject to change without notice.
Please check our website to ensure you have the latest version of this document.

©2020 HeatLink Group Inc.

This page is intentionally blank.