Job or Customer :	
Location :	
Engineer :	
☐ Complies with Spec ☐ Alternate	Notes :
Contractor :	
HeatLink Rep :	
Submitted By :	Date :
Approved By :	Date :
P.O. Number :	Date :

Description


Solid no lead (Eco) Brass PEX F1960 tees for PEX-a potable water expansion systems.

The use of PEX tubing in a potable hot-water plumbing system with an operating temperature above 140°F (60°C) or system pressure above 80 psig (550 kPaG) or highly aggressive water quality or any combination thereof can significantly reduce the service life of the tubing.

HeatLink requires following the guidelines described in Plastics Pipe Institute TN-53, Guide to Chlorine Resistance Ratings of PEX Pipes and Tubing for Potable Water Applications and HeatLink INFO 37, Domestic Hot Water Recirculation Systems.

PEX F1960 Tees

Qty	Stk. #	Size (run × run × branch)	Dimension, in/(mm) A	B	C	D	E	F	G	ID1	ID2	ID3	Weight, lb/(kg)
	EX26555NL	½" × ½" × ½"	0.70 (17.8)	0.32 (8.1)	0.32 (8.1)	0.70 (17.8)	0.30 (7.6)	0.50 (12.7)	0.70 (18.1)	0.40 (10.2)	0.40 (10.2)	0.40 (10.2)	0.132 (0.060)
	EX26222NL	¾" × ¾" × ¾"	0.95 (24.1)	0.45 (11.4)	0.45 (11.4)	0.95 (24.1)	0.47 (11.9)	0.64 (16.3)	0.95 (24.1)	0.60 (15.2)	0.60 (15.2)	0.60 (15.2)	0.293 (0.133)
	EX26888NL	1" × 1" × 1"	1.18 (30.0)	0.73 (18.5)	0.73 (18.5)	1.18 (30.0)	0.59 (15.0)	0.73 (18.5)	1.18 (30.0)	0.80 (20.2)	0.80 (20.2)	0.80 (20.2)	0.445 (0.202)



Technical Data

	Specifications
Material	No Lead (Eco) Brass - C69300
Operating pressure rating	180ºF @ 100 psi (82.2ºC @ 0.69 MPa)

Listings
ICC-ES PMG 1087
cNSFus-pw
cQAlus P371
U.P. Code


Codes
IMC
IPC
IRC
NPC of Canada
NSPC
UMC
UPC

Standards
ASTM E84
ASTM F877
ASTM F1960
CSA B137.5
NSF/ANSI 14
NSF/ANSI 61
NSF/ANSI 372
ULC S102.2

©2024 HeatLink Group Inc.

PEX F1960 Reducing Tees

Qty	Stk. #	Size (run × run × branch)	Dimension, in/(mm)										Weight, lb/(kg)
			A	B	C	D	E	F	G	ID1	ID2	ID3	
	EX26255NL	¾" × ½" × ½"	0.94 (24.0)	0.45 (11.5)	0.45 (11.5)	0.71 (18.0)	0.47 (12.0)	0.57 (14.5)	0.71 (18.0)	0.60 (15.2)	0.38 (9.7)	0.38 (9.7)	0.205 (0.093)
	EX26252NL	¾" × ½" × ¾"	0.90 (22.9)	0.45 (11.4)	0.45 (11.4)	0.70 (17.8)	0.50 (12.7)	0.60 (15.2)	0.90 (22.9)	0.60 (15.2)	0.40 (10.2)	0.60 (15.2)	0.264 (0.120)
	EX26225NL	¾" × ¾" × ½"	0.90 (22.9)	0.45 (11.4)	0.45 (11.4)	0.90 (22.9)	0.50 (12.7)	0.70 (17.8)	0.70 (17.8)	0.60 (15.2)	0.60 (15.2)	0.40 (10.2)	0.283 (0.128)
	EX26822NL	1" × ¾" × ¾"	1.20 (30.5)	0.56 (14.2)	0.56 (14.2)	0.90 (22.9)	0.60 (15.2)	0.80 (20.3)	0.90 (22.9)	0.80 (20.3)	0.60 (15.2)	0.60 (15.2)	0.455 (0.206)
	EX26885NL	1" × 1" × ½"	1.18 (30.0)	0.45 (11.5)	0.45 (11.5)	1.18 (30.0)	0.59 (15.0)	0.73 (18.5)	0.71 (18.0)	0.80 (20.2)	0.80 (20.2)	0.38 (9.7)	0.331 (0.150)
	EX26882NL	1" × 1" × ¾"	1.20 (30.5)	0.56 (14.2)	0.56 (14.2)	1.20 (30.5)	0.60 (15.2)	0.80 (20.3)	0.90 (22.9)	0.80 (20.3)	0.80 (20.3)	0.60 (15.2)	0.492 (0.223)



Installation

Installation must follow all of HeatLink's instructions and guidelines.

Related Documents

- F1960 PEX-a Potable Water Expansion System Installation Guide (L3240)
- HeatLink Limited Plumbing Warranty

All information is subject to change without notice.
Please check our website to ensure you have the latest version of this document.

©2024 HeatLink Group Inc.